Nucor Accent Wall Metal Wall Panel System



1-1/4"

12"

The architectural features of the Nucor Accent Wall make it ideal for fascias and decorative wall designs. The recessed fasteners provide a clean exterior appearance, and the deep rib configuration creates an attractive shadow pattern. Fasteners for are semi-concealed.

Panel Credentials

- ASTM E283 Test Method for Determining Air Leakage Through Wall Systems
- ASTM E331 Test Method for Water Penetration of Exterior Wall Systems
- State of Florida Product Approval
- UL263 Fire Tests of Building Construction and Materials
- ASTM C1363-11 Test Method for Thermal Performance of Building Materials and Envelope Assemblies by Means of a Hot Box Apparatus

Panel Specifications							TOP IN COMPRESSION		BOTTOM IN COMPRESSION	
Gage	Thickness (in.)	Yield (ksi)	Tensile (ksi)	Panel Wt. (psf)	l× (Gross) (in⁴)	S× (eff.) (in³)	M₁ (kip-in)	S× (eff.) (in³)	Mª (kip-in)	
26	0.0177	80	82	0.86	0.0320	0.0417	1.500	0.0367	1.3167	
24	0.0222	80	82	1.08	0.0400	0.0537	1.9267	0.0493	1.7700	

Panel Capacity (psf)

	<u>26 G</u>	AGE	<u>24 GAGE</u>		
SPAN (ft.)	Pressure ⁷	Suction ^{4,8}	Pressure ⁷	Suction ^{4,8}	
3.0	78	72	119	91	
3.5	67	62	102	78	
4.0	58	54	89	68	
4.5	52	48	72	61	
5.0	43	43	59	55	
5.5	36	40	48	50	
6.0	30	34	41	44	
6.5	26	29	35	38	
7.0	22	25	30	33	
7.5	19	22	26	28	

NOTES

Section properties were calculated in accordance 1. with AISI S100/CSA S136, 2016 Edition.

36"

12"

12"

- 2. Panels were checked for bending, shear, combined bending and shear, web crippling, deflection and panel pullover.
- 3. Deflection is limited to Span/60.
- Panel pullover limits are based on d'w = 0.44". 4
- 5. Thermal load has not been considered.
- 6. Capacities are based on a 3-span condition with equal length spans.
- 7. "Pressure" load is applied inward on the outer surface towards supports.
- 8. "Suction" load is applied outward on the inner surface away from panel supports.